



is800

The Tidel *is800* represents the newest edition of our low-end focus function ATMs designed exclusively for off-premise use. The *is800* sets a new standard of affordability without compromising quality and performance.



Tidel Engineering, L.P.

2310 McDaniel Drive

Carrollton, TX 75006

Phone: 972.484.3358

1.800.678.7577

Fax: 972.484.1014

E-mail: sales@tidel.com

www.tidel.com

Specifications:

Weight: 280 Lbs.

Power Requirements: 100-250v A/C 50/60Hz, 2.6 AMP.

Power Supply: 50 watt with easy access A/C plug.

Power Connections:

Unit recommended to be connected to a dedicated power circuit consisting of "Line", "Neutral" and "Ground" leads connected directly to the power distribution panel.

Phone Line Requirements:

Unit must be connected to a dedicated "tone" or "pulse" telephone that is terminated with a standard wall jack (RS-11C). To insure expected connectivity, unit should not share this line with any other equipment.

[s] standard features

[u] optional upgrades

Modem

[s] Standard modem

[u] 33.6 baud modem upgrade



Cabinet

[s] UL291 Classified (short-door)



Dispenser
[s] LG Mini CDM single cassette dispenser (800-note capacity)



Other Options
[u] Surge suppressor
[u] Potted Encryption Board for greater tamper resistance

Display
[s] Monochrome display
[u] Color display

